




### Features

- 27" FHD Display Kiosk with PCAP Touchscreen
- Intel® Core™, Pentium®, Celeron® Processors
- Windows and Android OS Supported
- Optional Scanner, MSR/SCR, NFC, Printer, Camera
- Modular Design for Effortless Setup
- Quick Access to Components for Easy Maintenance
- Flexible Installation on a Floor, a Wall or a Table
- Compact, Slim, Elegant
- Customizable for Individual Business Needs

### Specifications

	Windows	Android	
System	<b>Processors</b>	Intel® Core™ i5-7200U (3M Cache, Up to 3.1GHz, 2 Cores) Intel® Pentium® 4415U (2M Cache, 2.3 GHz, 2 Cores) Intel® Celeron® J1900 (2M Cache, Up to 2.42 GHz, 4 Cores), Fanless	Cortex™- A17 Quad-Core (Up to 1.8GHz)
	<b>Chipset</b>	ITE Tech IT8786E (Core/Pentium) Intel® Bay Trail (Celeron)	
	<b>Memory</b>	4GB Standard, DDR4 2133 MT/s, Socket 1x SODIMM (Max. 16GB) (Core/Pentium) 4GB Standard, DDR3L 1600 MT/s, Socket 1x SODIMM (Celeron)	1GB Standard, DDR3L 1600 MT/s, On-board (Max. 2GB Optional)
	<b>Storage</b>	SATA 3 (6Gb/s) 2.5 inch SSD 64GB, Support AHCI (Core/Pentium) SATA 2 (3Gb/s) 2.5 inch SSD 64GB, Support AHCI (Celeron)	eMMC 8GB, On-board, (Max. 64GB Optional)
	<b>Operating Systems</b>	Windows 7, Windows 8.1, Windows 10 IoT Enterprise, POS Ready 7	Andoird 7X (Nougat)
	<b>Audio</b>	Realtek ALC662-VD	Realtek ALC5640
Display	<b>Type</b>	27" TFT LCD, LED Backlight	
	<b>Resolution</b>	1080 x 1920	
	<b>Brightness</b>	300 cd/m <sup>2</sup> (typ.)	
	<b>Touchscreen</b>	Projective Capacitive Touch	
	<b>Response</b>	12 ms	
	<b>Contrast Ratio</b>	3000 (typ.)	
Interface	<b>USB</b>	Core/Pentium 6 (Rear 2, Back 4, USB 3.0 x 2, USB 2.0 x 4) 3 (Reserved for MSR, SCR, i-Button/Touch Controller/Camera), RJ-45 Celeron 6 (Rear 2, Back 4, USB 2.0 x 6) 3 (Reserved for MSR, SCR, i-Button/Touch Controller/Camera), RJ-45	6 (Rear 2, Back 4, USB 2.0 x 6) 3 (Reserved for MSR, SCR/ Touch Controller/Camera), RJ-45
	<b>Serial</b>	6 (COM 1 with 5V/12V Power Output on 9 Pins, BIOS, Reserved for NFC) (COM2~3 RJ-45, Full Signal), Reserved for Cash Module) (COM4 RJ-11, Only TX/RX, 12V Power Output, Reserved) (COM5 Reserved for Printer) (COM6 RJ-45, Only TX/RX, 5V Power Output, Reserved for MSR, IC Card)	
	<b>LAN</b>	1x Gigabit Ethernet, RJ-45	
	<b>Power DC-IN</b>	1x (3 Pin Connector)	
	<b>Power Supply</b>	Adaptor 24V, 6A	
	<b>Material</b>	Galvanized Steel Plate	
Pedestal	<b>Material Thickness</b>	1.2T	
	<b>Component Access</b>	Security Locks with 7-Pin Tumbler / Rear Security Door	
Physical & Environmental	<b>Operating Temperature</b>	0 °C ~ 60 °C at 10% to 90% Humidity	
	<b>Storage Temperature</b>	-20 °C ~ 80 °C at 10% to 90% Humidity	
	<b>Dimensions (W x H x D)</b>	42.6x 178 x 13.5 cm, 16.7 x 70.0 x 5.3 in	
	<b>Packing Dimensions (W x H x D)</b>	100 x 57 x 26 cm, 39.3 x 22.4 x 10.2 in (System) 100 x 57 x 26 cm, 39.3 x 22.4 x 10.2 in (Pedestal, Baseplate)	
	<b>Net Weight</b>	36kg, 79.3lb (System, Pedestal, Baseplate)	
	<b>Packing Weight</b>	43kg, 94.7lb (System, Pedestal, Baseplate)	
	<b>Certification</b>	CE, FCC, KC	
	<b>Color</b>	High Gloss White, High Gloss Black, Custom Colors Available	
Options	<b>Storage</b>	2.5 inch SSD 128GB, HDD 500GB, 1TB	
	<b>Built-in Printer</b>	3" Jam-Free Thermal, Max. 250mm/s, Auto Cutter (Interface : Serial, USB)	
	<b>Barcode Scanner</b>	1D, 2D Barcode	
	<b>Camera</b>	2M USB Interface (Internal) (Factory Option)	
	<b>Magnetic Stripe Reader</b>	Comply with ISO 7811, Support 1 & 2 & 3 Track	
	<b>Smart Card Reader</b>	EMV Level 1, 2	
	<b>NFC Reader</b>	MIFARE, FeliCa, ISO/IEC 14443A, ISO/IEC 14443B, ISO/IEC 15693	
	<b>Wall Mount Kit</b>	VESA-Compatible, 100 x 100 mm, 200 x 200 mm	
	<b>Speaker</b>	2 x 5W (Stereo) (Factory Option)	
	<b>WiFi</b>	Mini PCIe for Wireless LAN (Core/Pentium) USB Dongle (Celeron)	On Board (Factory Option)
	<b>Custom Options</b>	Customer-Assigned EMV Terminal Bracket, Bill/Coin Acceptor, Document Reader (Passports/IDs), Ticket/Document Printer, UPS (Uninterruptible Power Supply)	


## Dimensions



## Applications

- Self-Service Kiosk in Retail and Hotel Segments
- Self-Order and Payment Kiosk in QSR
- Theater/Museum Ticket Kiosk
- Document Scanning/Printing Kiosk

## Options



### Payment

- MSR/SCR, Bill/Coin Acceptor
- Customer-Assigned EMV Terminal Bracket




### Built-in Printer

- 3", Speed up to 250 mm/s, Auto Cutter



### Barcode Scanner

- 1D, 2D Barcode



### NFC

- MIFARE, FeliCa, ISO/IEC 14443A
- ISO/IEC 14443B, ISO/IEC 15693