

T2248



Tally

High-speed printing - At 10 cpi, print speed ranges from 113 cps for letter quality to 432 cps for high speed draft quality. A 24 pin print head offers high speed with excellent quality.

Software compatibility - Compatible with the IBM Proprinter XL24E and Epson ESC/P2 command sets.

Multiple fonts - The printer has nineteen resident fonts: Ten bitmap fonts - Courier 10, Pica 10, Prestige Elite 12, Boldface PS, OCR-B, OCR-A, Correspondence, Compressed, Draft and High-speed Draft, and nine outline fonts - Timeliness, Nimbus Sans and Courier, each in upright, italic and bold.

Highlights at a glance:

- 80 column
- Auto tear off
- Auto load
- Printhead protection
- Parallel & USB interface as standard
- Optional Lan interface
- Auto interface switching on multiple I/F versions

Large print buffer - 128k bytes are available in total for strong input data and downloading fonts. A large input data buffer allows you to send files to the printer and return quickly to your application.

Simple switching of paper types & Auto tear-off - Parking continuous forms makes it easy to switch between continuous forms and single sheets. Continuous forms are automatically fed up to the tear-off position at the end of each job.

Maintenance free - Periodic cleaning and changing the ribbon cartridge are all that's required.

Configurations:

- **T2248** Standard Product

T2248

Print Speed	480 cps (Fastest Draft); 360 cps (Draft), 113 cps (LQ) at 10 cpi
Resolution	up to 360 x 360 dpi
Throughput (ECMA 132)	319 pages per hour
Character Density	10, 12, 15, 17.1, 18, 20 cpi
Line Density	1, 2, 3, 4, 6, 8 lpi
Printhead Life	400 million strokes
Memory	128 kB
Standard Connectivity	Parallel (Bi-directional) and USB 1.1
Standard Emulation	IBM ProPrinter XL24E, Epson ESC P/2
Fonts	Courier, Prestige, Elite, Boldface, Compressed, Draft, HS Draft, Correspondence Pica, Nimburs Sans®, Timeliess, OCR-A/B
Consumables	Ribbon: 4 million characters
Standard Paper Handling	Push tractor and cut sheet insertion
Number of Copies	1 original + 5 copies
Paper Type	Cut sheets, continuous forms, multi-part forms
Paper Weight	60-120 g/m ²
Paper Size	Width: 102 to 267 mm; Length: 76 to 364 mm
Physical Weight	7,3 kg
Physical Size	415 x 330 x 120 mm (W x D x H)
Acoustic	49 dB(A)
Power Voltage	230 V - 50/60 Hz
Power Consumption	10 Watt Stand-By
Temperature	+5° to +35° C; 20% to 80% humidity
Workload	7.000 pages per month
MTBF	20.000 hours
Drivers	Windows 2000/XP/Vista/7/8 and Server 2003/2008

DASCOM GB Limited

Hart House, Priestley Road

Basingstoke, Hampshire RG24 9PU

Tel: +44 1256 355130 – Fax: +44 1256 481400

info.gb@dascom.com – www.dascom.com

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 