



MICUS10 PLUS

All-in-one Touch POS



15" Touch Panel POS System
Fanless Operation
Ultra Low Power System
VESA Mount (75mm)
Optional Wireless Lan Module



All-in-one Touch POS

Specifications

System

CPU & Chipset	Intel® Atom™ D2550 1.86GHz (Dual Core), Intel® NM10
Memory	2GB DDR3 SoDIMM (up to 4GB)
HDD	SATA-II 320GB↑ / SSD 32GB↑
Display & Touch	15" TFT LCD (1024 x 768), 5-wire Analog resistive Touch Panel
External I/O	2 x PS/2, 4 x COM, 2 x LAN, 1 x VGA, 1 x LPT, AUDIO, 4 x USB 2.0
Speaker	Built-in Speaker 1W
OS Supported	Microsoft® POSReady2009 / POSReady7 Windows XP / Windows 7 / Linux

Power Supply Unit

Power Input	External adaptor DC12V 5A (60W)
Power Output	YES (12V, 0.5A)

Environment & Mechanical

Dimension (WxDxH)	F type : 440 x 87 x 303 (mm) S type : 388 x 188 x 305 (mm)
Weight	F type : 4.3 kg / S type : 5.4 kg
Housing Color	Black
Mounting	VESA Compliance (75mm)
Fanless Operation	YES

Optional

Magnetic Stripe Reader	ISO Track2 / Track 1&2 / Track 1&2&3
Wireless Lan	802.11n, 150Mbps↑ (Internal USB Module)
Customer Display	Dual Monitor 9.7", 15"/ CDP(20CharX2Lines)
Recovery Solution	System Image BackUp Solution
iButton Reader	USB type, Magnetic type
Smart Card Reader	USB type, EMV Level1

* Design and Specifications are subject to change without notice.



MICUS10 PLUS



AUTHORISED DEALER

HANASIS Co., Ltd.

#517 Anyang Mega Valley, 799, Gwanyang-dong, Dongan-gu, Anyang-si, Gyeonggi-do, 431-767 Korea
Tel. 82-31-426-4343, 4342 / Fax. 82-31-426-4381 / <http://www.hanasis.com>