

HS-S02A Series!

so **Mighty** so **Cute** so **Slim**

It's your first choice!

New generation in POS, HANASIS!



160G HDD
Flexible Chipset Usage
5 USB ports / 4 Serial ports

HANASIS
System Integration Supplier

HS-S02A Series!



HS-S02A

Content	Specification
CPU	Intel Celeron Conroe L430 upto Intel Core2Duo
Memory	1GB (Max. 4GB)
Hard disk	160GB 2.5" SATAII or 16GB SSD
Display Size	15 inch
Touch Type	5-Wire, Resistive
Resolution	1024 X 768
LCD Brightness	250 cd/m ²
MSR	Track II (Option : Track I, II / Track I,II,III)
Serial Port	4 EA
Parallel Port	1 EA
USB Port	5 EA (Default : Front 1EA, Rear 4EA)
Ethernet	1 EA
PS2 Port	2 EA
Cash Drawer Port	None
Audio Port	Yes
Operating System	Microsoft POSReady 2009 / WEPOS / XP / CE, LINUX
Power Supply	AC 100-240VAC, 220W
Dimension	395 X 370 X 340 (W X L X H mm)
Option	15" Dual Monitor (1024X768, RGB Type) 7" Dual Monitor (800X480, USB Type) DVR Wall Mountable

HS-S25A(Fanless)

Content	Specification
CPU	Atom N270 (1.6GHz)
Memory	1GB (Max. 2GB)
Hard disk	160GB 2.5" SATAII or 16GB SSD
Display Size	15 inch
Touch Type	5-Wire, Resistive
Resolution	1024 X 768
LCD Brightness	250 cd/m ²
MSR	Track II (Option : Track I, II / Track I,II,III)
Serial Port	4 EA
Parallel Port	1 EA
USB Port	5 EA (Default : Front 1EA, Rear 4EA)
Ethernet	2 EA
PS2 Port	2 EA
Cash Drawer Port	None
Audio Port	Yes
Operating System	Microsoft POSReady 2009 / WEPOS / XP / CE, LINUX
Power Supply	DC 12V, 5A
Dimension	395 X 370 X 340 (W X L X H mm)
Option	15" Dual Monitor (1024X768, RGB Type) 7" Dual Monitor (800X480, USB Type)

<http://www.hanasis.com>