

The Latest 80mm P13 Series Thermal Printer
Support USB+COM+Ethernet Three Interface

3" RECEIPT THERMAL PRINTER

Model: P13-USL

High reliability and easy operation for busy applications



Receipt Thermal Printer P13 Series

The P13-USL is a high performance but economic model featuring excellent reliability and easy operation. With printing speed up to 300 mm / sec, easy paper replacement and less paper jams, it can satisfy crowded check-out line and promotional activities in the peak hours. Additionally, the P13-USL features flexible deployment in the wall-mount design for better space arrangement. The P13-USL showcases high reliability and easy operation for busy applications.

Quality and Reliability

- Compatible with two command sets of ECS/POS and Star
- Support 2D barcode printing
- High speed of 300mm/sec with USB+Serial+LAN three interface
- USB Virtual COM interface
- Kitchen printing and network printing
- Paper end detection
- Printing and error alarm function
- Network status monitoring, and multiple connection
- OPOS driver
- Printer authentication and software bundle
- Variety of international language character sets
- Serial port, USB, LAN and 24V RJ11 for cash drawer drive



Interface
(USB, Serial, Ethernet, RJ11, DC-in)





Bar



Super Market



Ticket



Retail



Hospitality



Hospital



Logistics



Warehouse



Financial



Jewelry Store

High-speed, high-resolution text and graphics printing

Now you can speed customer throughput with the P13 printer. It prints both receipts and graphics at the same high speed of up to 300mm per second. And it's the first printer in the industry to offer 16 levels of grayscale to ensure clear, crisp graphics.

Reliability you can count on

With a MCBF of 150 km, and an autocutter life of 2 million cuts, the P13 delivers best-in-class reliability so critical in high volume environments.

Easy to use. Easy to maintain.

The P13 is packed with easy-to-use features including drop-in paper loading, an autocutter, easy-to-read LEDs and an improved cover design to protect the printer from foreign objects.

More features, more flexibility

The P13 also features auto speed adjustment for smoother printing, margin and line reduction functions to reduce paper usage and costs, and more barcode options. In addition, it comes with three interfaces (COM, USB and Ethernet interface) for flexibility in handling interface transitions.



Wall-mountable



2D Barcode



Alarm



Easy Paper



Portable



Hi-speed



Rich Interface



Variety Paper



Autocutter

SPECIFICATIONS

Model	P13-USL
Printing Method	Line Thermal
Resolution	576Dots/Line or 512Dots/Line
Character Size	ANK, Font A: 12×24dots, Font B: 9×17Dots Simplified Chinese, Traditional Chinese: 24×24Dots
1D Bar Code	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
2D Bar Code	QR CODE
Interface	Serial+USB+LAN Port
Power Supply	DC 24V/2.0A
Cash Drawer Port	Default RJ11, 24VDC/1A
AutoCutter	Partial cutter
Printing Head Life	150Km
Working Environment	Temperature (0~45°C) Humidity(10~80%)
Storage Environment	Temperature (-10~60°C) Humidity(10~90%)
Printing Speed	300mm/sec
Paper Width	79.5±0.5mm
Paper External Diameter	φ 83mm
Paper Thickness	0.06-0.08mm
Weight	1.30Kg
Dimension	140X180X125mm(WxDxH)

* Sinocan reserves the right to change the specification without prior notice.

Sinocan International Technologies Co., Ltd.

4th Floor, Future Plaza, Overseas Chinese Town,
Nanshan Distr. Shenzhen, China 518053
Factory: A8 Building, Peking University Founder
Shiyan Science Park, Bao'an, Shenzhen, China 518108
Tel: +86-755-2691 5588 Fax: +86-755-8661 2352
Email/MSN: info@sinocan.com.cn
Skype: sales.sinocan
Web site: http://www.sinocan.com.cn
Global Service Hotline: +86-400-6600060

