

# T06B-15

## TOUCH SCREEN MONITOR



**The most cost-effective touch solutions for your business**  
**A wide range of connectivity to meet numerous applications.**

### Touch Monitor T06 Series

The solid touch POS monitor with an easy use and fashionable design, T06B-15 features an artistic 15" touch monitor and supports applications with the choice of MSR and VFD customer display. It's fashionable design makes it compatible with numerous spaces such as retail, restaurant shop or hospitality sector. In addition, the robust structure with front IP65 proves it's capable to resist any harsh environments.

#### Quality and Reliability

- Long lasting product cycle-enclosure controlled by Sinocan
- Specifications
- 5-Wires resistive touch panel
- 75 x 75mm VESA mounting holes in center
- Touch controller has USB and RS232 dual interface
- Flexible to adjust angle 0-90 degree
- Multilingual on-screen display (OSD)

#### Innovation and Application

Meets VESA 75mm x 75mm and versatile peripheral options such as MSR, customer pole display, programmable keypad and a wide range of connectivity to meet numerous applications.



# SPECIFICATIONS

<b>Model</b>	T06B-15
<b>Diagonal Size</b>	15" 4:3
<b>Touch Technology</b>	5-wires Resistive Touch Panel, Life: 10 Million Touches
<b>Touch Interface</b>	Dual USB & RS232 Interface or Single USB Interface Option
<b>OS Support</b>	Windows XP, Vista, 7, XPe, CE and iMAC, Linux, DOS, QNX
<b>Useful Screen Area</b>	34 mm (H) x 228 mm (V)
<b>Monitor Dimensions (without stand)</b>	374(L)×70(W)×303(H)(mm)
<b>Native (optimal) Resolution</b>	1024 X 768 @ 60 Hz
<b>Colors</b>	16.7 Million
<b>Brightness(typical)</b>	LCD Panel: 250 nits
<b>Response Time - total (typical)</b>	8 msec
<b>Viewing Angle (typical)</b>	Horizontal: ±80° or 160° Total
<b>Contrast Ratio (typical)</b>	600:1
<b>On-screen Display (OSD)</b>	Controls (front): Auto, -, +, Menu, Power Settings: Contrast, Brightness, H/V Position, RGB (color Temp), Clock, Phase, Recall Languages: English, German, Spanish, Japanese, French, Russian, Chinese
<b>Input Video Signal Connector</b>	D-sub 15-pin VGA Type
<b>Audio</b>	2 X Built-in Speakers (*option)
<b>Power Supply</b>	External Power Adaptor 50W; AC: 100~240V, 50/60Hz; DC: +12VDC, 4.16A
<b>Power Consumption (typical)</b>	<30 W
<b>Mounting Application</b>	75 mm VESA Mount
<b>Weight</b>	N.W.:4.51Kg / G.W.:6.42Kg
<b>Other Features</b>	Security Lock Receptacle
<b>Temperature</b>	Operating: 0°C To 40°C (32°F To 104°F), Storage: -20°C To 60°C (-4°F To 140°F)
<b>Humidity(noncondensing)</b>	95% @ 60°C
<b>Options</b>	3-Tracks Magnetic Stripe Reader, USB interface Wall Mount Or Ceiling Mount Brackets

\* Other model's specs, please visit [http://www.lcdpc.com.cn/Pro\\_LCD\\_TouchScreen\\_Monitor.php](http://www.lcdpc.com.cn/Pro_LCD_TouchScreen_Monitor.php)  
\* Sinocan reserves the right to change the specification without prior notice.



## Sinocan International Technologies Co., Ltd.

4F, Xiangnian Square, Overseas Chinese Town,  
Nanshan Distr. Shenzhen, China 518053  
Factory: A8 Building, Peking University Founder  
Shiyan Science Park, Bao'an, Shenzhen, China 518108  
Tel: +86-755-26915588 Fax: +86-755-86612352  
Email/MSN: marketing@lcdpc.com.cn  
Skype: marketing\_lcdpc  
Web site: <http://www.lcdpc.com.cn>  
Global Service Hotline: +86-400-6600060

**SINOCAN**  
Global OEM/ODM Manufacturer